



VERSUS

master painters &
coating specialists

CK 200205166623

ACRYLIC FIRSTCOATER

PRODUCT DATA SHEET

Valdisole

704 - 706 6th Street

Wynberg

Santon 2090

Tel: (011) 885 3136

Fax: (011) 885 1719

1. RECOMMENDED USES

- 1.1. A quality acrylic Firstcoater for use on interior and exterior cement plastered walls. Can also be used on fibre cement and plasterboard ceilings. It provides exceptional hiding power and opacity.

2. PREPARATION

- 2.1. Surfaces must be clean and free from loose material.

3. APPLICATION

- 3.1. With either a sheepskin roller or brush.
3.2. For best results do not thin.

4. PRODUCT DATA

TYPE	Styrene Acrylic
DFT/Coat	Min 35µm. Max 45µm
DRYING TIME	Surface Dry ½ - 1 Hours Hard Dry 3hours at 25°C
VISCOSITY	100 - 110 Kneb Units
RELATIVE DENSITY	1.40 -1.42
SOLIDS BY MASS	55%
SPREADING RATE	4 - 8m ² /Litre depending on surface porosity and texture.
FINISH	Matt
CLEANUP	Water

5. COLOUR

- 5.1. Available in white and pastel colours.

6. PRECAUTIONS

- 6.1. Do not apply to bare (unprimed) metal surfaces.
6.2. Avoid painting in wet or cold weather (Minimum 8° Celcuis)
6.3. When painting ceilings ensure that nails heads are primed and undercoated before applying.

DISCLAIMER

The above information is given in good faith but without warranty due to the fact that the methods off application, location and condition of the substrates being coated are beyond our control.