



VERSUS

master painters &
coating specialists

CK 200205166623

AQUARIPPLE

Valdisole

704 - 706 6th Street

Wynberg

Santon 2090

Tel: (011) 885 3136

Fax: (011) 885 1719

PRODUCT DATA SHEET

1. RECOMMENDED USES

- 1.1. A rounded ripple textured wall coating used as a basecoat or top coat producing a tough finish which covers hairline cracks and minor plaster imperfections.
- 1.2. An ideal product for use in high traffic areas.
- 1.3. Can be used in conjunction with fibreglass membranes as a waterproofing compound.
- 1.4. Can be overcoated with most waterbased acrylic finishes.

2. PREPARATION

- 2.1. Surfaces must be clean and free from loose material.
- 2.2. Surfaces should be correctly primed utilising surface preparation specifications recommended by the manufacturers.
- 2.3. May be applied directly onto cleaned previously painted surfaces.

3. APPLICATION

- 3.1. With a sheepskin roller or a honeycomb sponge roller.

4. PRODUCT DATA

TYPE	Modified Acrylic
WATER RESISTANCE	Excellent
DRYING TIME	Hard Dry 18 hours at 25°C Overcoating time 24 hours plus.
VISCOSITY	Thixotropic Paste
RELATIVE DENSITY	1.30 - 1.35
SOLID BY MASS	55%
SPREADING RATE	±3m ² /l (typical) depending on surface porosity and texture.
FINISH	Satin Sheen Texture.
CLEANUP	Water

5. COLOUR

- 5.1. White.
- 5.2. Pastel and Medium colours can be tinted on request.

6. PRECAUTIONS

- 6.1. Do not apply to bare (unprimed) metal surfaces.
- 6.2. Avoid painting in wet or cold weather (Minimum 8° Celcius)

DISCLAIMER

The above information is given in good faith but without warranty due to the fact that the methods of application, location and condition of the substrates being coated are beyond our control.