



VERSUS

master painters &
coating specialists

CK 200205166623

BRICK DRESSING

PRODUCT DATA SHEET

Valdisole
704 - 706 6th Street
Wynberg
Santon 2090
Tel: (011) 885 3136
Fax: (011) 885 1719

1. RECOMMENDED USES

- 1.1. For use on dry, face or standard brickwork, stone and quarry stone surfaces.
- 1.2. Has a durable glossy finish.

2. PREPARATION

- 2.1. Surfaces must be clean, dry and free from loose or flaking material.
- 2.2. New brick and stone work must be allowed to age and dry out for \pm 2 months.

3. APPLICATION

- 3.1. With either a roller or brush.

4. PRODUCT DATA

TYPE	UV Stabilised Alkyd
DRYING TIME	Surface Dry 3-4 Hour Hard Dry 16-18 hours at 25°C
VISCOSITY (Ford Cup)	30Secs Ford 4 @ 25°C
RELATIVE DENSITY	0.85 - 0.90
SPREADING RATE	8m ² /l (typical) depending on surface porosity and type.
FINISH	Gloss
CLEANUP	Mineral Turps

5. COLOUR

- 5.1. Clear

6. PRECAUTIONS

- 6.1. Do not apply to damp surfaces.
- 6.2. Do not paint in wet or cold weather (Minimum 8° Celcius)
- 6.3. Not suitable for use on slasto floors.

DISCLAIMER

The above information is given in good faith but without warranty due to the fact that the methods off application, location and condition of the substrates being coated are beyond our control.