



VERSUS

master painters &
coating specialists

CK 200205166623

Valdisole

704 - 706 6th Street

Wynberg

Santon 2090

Tel: (011) 885 3136

Fax: (011) 885 1719

CHROME ALUMINIUM PAINT

PRODUCT DATA SHEET

1. RECOMMENDED USES

- 1.1. A single pack high quality aluminium finish for use on various surfaces both internally and externally. Ideal for use on suitably primed and undercoated metal surfaces. Has excellent protection against ultra violet light.

2. PREPARATION

- 2.1. Surfaces must be clean and free from loose material.
- 2.2. New work should be correctly primed and undercoated dry out for ± 2 months.
Steel: Apply 1 coat metal primer or zinc phosphate primer.
Galvanised steel: first wash with a galvanised iron cleaner then apply 1 coat galvanised iron primer or as recommended by the manufacturer.
- 2.3. Can be applied over previously painted surfaces in sound condition.

3. APPLICATION

- 3.1. With either a short nap mohair roller or brush. For conventional and airless spray thin with minimum amount of mineral turpentine (max 10% for spraying).
- 3.2. Ensure that the product is well stirred with a flat paddle until homogeneous stir occasionally during use.

4. PRODUCT DATA

TYPE	Long Oil Alkyd
DFT\Coat	Min 20 μ m. Max 30 μ m
DRYING TIME	Surface Dry 4 Hour Hard Dry 18 hours at 25°C
VISCOSITY	65-70Ku
SPECIFIC GRAVITY	1.08-1.2
SOLIDS	64% - 66% by mass.
SPREADING RATE	8 -10 m ² /l (typical) depending on surface porosity and type
FINISH	Leafing aluminium
CLEANUP	Mineral Turpentine

5. COLOUR

- 5.1. Silver only

6. PRECAUTIONS

- 6.1. Do not apply to bare (unprimed) metal surfaces.
- 6.2. Do not paint in wet or cold weather (Minimum 5°C or above 35°C)

DISCLAIMER

The above information is given in good faith but without warranty due to the fact that the methods of application, location and condition of the substrates being coated are beyond our control.