



VERSUS

master painters &
coating specialists

CK 200205166623

GLAZECOAT

Valdisole

704 - 706 6th Street

Wynberg

Santon 2090

Tel: (011) 885 3136

Fax: (011) 885 1719

PRODUCT DATA SHEET

1. RECOMMENDED USES

- 1.1. For interior and exterior use as a glaze coat over any Versus water based finishes.
- 1.2. Can be used on interior and exterior brickwork to enhance appearance.

2. PREPARATION

- 2.1. Surfaces must be clean and free from loose or flaking material.
- 2.2. New brick and stone work must be allowed to age and dry out for ± 2 months.

3. APPLICATION

- 3.1. Can be applied with either a roller or brush.

4. PRODUCT DATA

TYPE	Acrylic Latex
DRYING TIME	Surface Dry 30 - 60 Mins Hard Dry 4 hours at 25°C
VISCOSITY	70 - 90 Krebs Units
RELATIVE DENSITY	0.98 - 1.00
SPREADING RATE	5 - 8 m ² /l (typical) depending on surface being overcoated
FINISH	Sheen
CLEANUP	Water

5. COLOUR

- 5.1. Clear only

6. PRECAUTIONS

- 6.1. Do not apply to damp surfaces.
- 6.2. Do not paint when ambient temperature is below 10°C.
- 6.3. Not suitable for use on wood or slasto floors.

DISCLAIMER

The above information is given in good faith but without warranty due to the fact that the methods of application, location and condition of the substrates being coated are beyond our control.