



VERSUS

master painters &
coating specialists

CK 200205166623

INTERIOR / EXTERIOR VARNISH

PRODUCT DATA SHEET

Valdisole
704 - 706 6th Street
Wynberg
Santon 2090
Tel: (011) 885 3136
Fax: (011) 885 1719

1. RECOMMENDED USES

- 1.1. As a general purpose interior / exterior varnish for use on all types of timber.
- 1.2. Not to be used as a wood floor coating.

2. PREPARATION

- 2.1. Woodwork surfaces must be clean, dry and well sanded.
- 2.2. First coat may be thinned with $\pm 10\%$ mineral turps.

3. APPLICATION

- 3.1. Brush only for best results.
- 3.2. Ensure that the product is well stirred.

4. PRODUCT DATA

TYPE	Long Oil Alkyd
DRYING TIME	Surface Dry 4 Hour Hard Dry 18 hours
VISCOSITY	65-70Ku
SPECIFIC GRAVITY	0.90 - 0.91
SOLIDS	45% by mass.
SPREADING RATE	10 -12 m ² /lt
FINISH	High Gloss or matt
CLEANUP	Mineral Turps

5. COLOUR

- 5.1. Available in gloss and matt finish.
- 5.2. Colours: clear, light oak, dark oak, teak and mahogany.

6. PRECAUTIONS

- 6.1. Do not apply to damp timber.
- 6.2. Do not paint in wet or cold weather (Minimum 5° Celcuis)
- 6.3. To prevent ingress of moisture the end grain must be coated.

DISCLAIMER

The above information is given in good faith but without warranty due to the fact that the methods of application, location and condition of the substrates being coated are beyond our control.