



VERSUS

master painters &
coating specialists

CK 200205166623

PREMIUM SHEEN ACRYLIC

PRODUCT DATA SHEET

Valdisole

704 - 706 6th Street

Wynberg

Santon 2090

Tel: (011) 885 3136

Fax: (011) 885 1719

1. RECOMMENDED USES

- 1.1. A high quality sheen finish flexible wall coating for interior and exterior use, providing excellent durability, weather resistance, colour stability, opacity and washability.
- 1.2. Ideal for high traffic areas or surfaces that may require frequent washing.

2. PREPARATION

- 2.1. Surfaces must be clean and free from loose material.
- 2.2. Surfaces must be primed correctly utilising surface preparation specifications recommended by the manufacturers.
- 2.3. May be applied directly onto cleaned previously painted surfaces.

3. APPLICATION

- 3.1. With either a sheepskin roller or brush.
- 3.2. Can be applied using an airless spraygun.

4. PRODUCT DATA

TYPE	Pure Acrylic
WATER RESISTANCE	Surpasses the SABS 0400:1900 Code of Practice rain penetration test over a 24 hour period.
DRYING TIME	Surface Dry ½ - 1 Hour Hard Dry 4 hours at 25°C
VISCOSITY	95- 100 Krebs Units
RELATIVE DENSITY	1.2 - 1.25
SOLID BY MASS	50 - 52%
SPREADING RATE	8 - 10m ² /Litre depending on surface porosity and texture.
FINISH	Sheen
CLEANUP	Water

5. COLOUR

- 5.1. Available in white and a range of 16 standard colours.
- 5.2. Pastel, Medium and Deep Tone can be tinted on request.

6. PRECAUTIONS

- 6.1. Do not apply to bare (unprimed) metal surfaces.
- 6.2. Do not paint in wet or cold weather (Minimum 8° Celcius)
- 6.3. When coating friable or powdery surfaces apply a penetrating coat of bonding liquid or Versaprime plaster primer.

DISCLAIMER

The above information is given in good faith but without warranty due to the fact that the methods of application, location and condition of the substrates being coated are beyond our control.