



VERSUS

master painters &
coating specialists

CK 200205166623

SUPAROOF

Valdisole

704 - 706 6th Street

Wynberg

Santon 2090

Tel: (011) 885 3136

Fax: (011) 885 1719

PRODUCT DATA SHEET

1. RECOMMENDED USES

- 1.1. A highly durable water based emulsion paint offering excellent adhesion and weathering when applied to correctly prepared galvanised iron, abestos and cement roof tiles.

2. PREPARATION

- 2.1. New galvanised iron must be thoroughly cleaned and primed with galvanised Galavanised Iron Primer.
2.2. All fungus, lichen or organic growth must be killed using fungicidal was and carefully removed by either wire brushing or highly pressure cleaning.

3. APPLICATION

- 3.1. By either roller, brush or airless spray.

4. PRODUCT DATA

TYPE	Va-Veova
DFT\Coat	Min 20µm. Max 30µm
DRYING TIME	Surface Dry ½ - 1 Hour Hard Dry 4 hours at 25°C
VISCOSITY	100 - 110 Kreb Units
RELATIVE DENSITY	1.30 - 1.40
SOLID BY MASS	50 -51% by mass.
SPREADING RATE	3 -8m ² /l (typical) depending on surface porosity and texture.
FINISH	Matt
CLEANUP	Water

5. COLOUR

- 5.1. Available in Venice Red, Black, Charcoal, Chocolate, Terracotta, Tuscany Plum, Heritage Green and Fadeless Green.

6. PRECAUTIONS

- 6.1. Do not apply to bare (unprimed) metal surfaces.
6.2. Avoid painting in wet or cold weather (Minimum 5° Celcuis)
6.3. During winter months in cold areas it is advisable to only apply to roofs between 10.00am and 3.00pm.

DISCLAIMER

The above information is given in good faith but without warranty due to the fact that the methods off application, location and condition of the substrates being coated are beyond our control.