



# VERSUS

master painters &  
coating specialists

CK 200205166623

## SUPER HIGH GLOSS ENAMEL

### PRODUCT DATA SHEET

Valdisole

704 - 706 6th Street

Wynberg

Santon 2090

Tel: (011) 885 3136

Fax: (011) 885 1719

#### 1. RECOMMENDED USES

- 1.1. A high quality enamel for use on various surfaces both internally and externally. Ideal for use on suitably primed interior plastered walls, wood and metal surfaces.

#### 2. PREPARATION

- 2.1. Surfaces must be clean and free from loose material.
- 2.2. New work should be correctly primed and undercoated with Universal Undercoat as recommended by the manufacturers prior to applying the top coats.
- 2.3. May be applied directly onto cleaned previously painted surfaces.

#### 3. APPLICATION

- 3.1. With either a short nap mohair roller or brush.
- 3.2. Ensure that the product is well stirred and do **not** thin.

#### 4. PRODUCT DATA

TYPE	Long Oil Alkyd
DFT\Coat	Min 20µm. Max 30µm
DRYING TIME	Surface Dry 4 Hour Hard Dry 18 hours at 25°C
VISCOSITY	65-70 Ku
SPECIFIC GRAVITY	1.08 - 1.2
SOLIDS	64 -66% by mass.
SPREADING RATE	8 -10m <sup>2</sup> /l (typical) depending on surface porosity and texture.
FINISH	High Gloss
CLEANUP	Mineral Turps

#### 5. COLOUR

- 5.1. Available in white and a range of colours.
- 5.2. Pastel, Medium and Dark Tones can be tinted on request.

#### 6. PRECAUTIONS

- 6.1. Do not apply to bare (unprimed) metal surfaces.
- 6.2. Do not paint in wet or cold weather (Minimum 5° Celcius)
- 6.3. When coating friable or plastered surfaces apply a generous coat of Alkali Resistant Plaster Primer.

#### DISCLAIMER

The above information is given in good faith but without warranty due to the fact that the methods off application, location and condition of the substrates being coated are beyond our control.