



VERSUS

master painters &
coating specialists

CK 200205166623

VERSABOND BONDING LIQUID

PRODUCT DATA SHEET

Valdisole

704 - 706 6th Street

Wynberg

Santon 2090

Tel: (011) 885 3136

Fax: (011) 885 1719

1. RECOMMENDED USES

- 1.1. For use as a clear alkali resistant sealer on gypsum plaster, cement plaster and porous, friable concrete surfaces.
- 1.2. May also be used as a sealer for masonite hardboard.

2. PREPARATION

- 2.1. All surfaces must be clean and dry. Moisture content of new plaster must be less than 12%.
- 2.2. Previously painted surfaces must be brushed down and any loose flaking paint must be removed.

3. APPLICATION

- 3.1. Ready for use with a roller or brush. Application by brush ensures penetration.

4. PRODUCT DATA

TYPE	Urethane
DRYING TIME	Surface Dry 2 Hour Hard Dry 8 hours at 25°C
VISCOSITY	15-18 Sec F4 @ 25°C
SPECIFIC GRAVITY	0.80 - 0.82
SOLIDS	±30%
SPREADING RATE	11 -12m ² /l (typical) depending on surface porosity and type.
CLEANUP	Mineral Turps

5. COLOUR

- 5.1. Clear.

6. PRECAUTIONS

- 6.1. Do not apply to metal surfaces.
- 6.2. Do not paint in wet or cold weather (Minimum 5° Celcius)
- 6.3. Should be overcoated within 48 hours to ensure adequate adhesion of the subsequent coats.

DISCLAIMER

The above information is given in good faith but without warranty due to the fact that the methods of application, location and condition of the substrates being coated are beyond our control.