



VERSUS

master painters &
coating specialists

CK 200205166623

Valdisole
704 - 706 6th Street
Wynberg
Santon 2090
Tel: (011) 885 3136
Fax: (011) 885 1719

VERSATHANE POLYURETHANE ENAMEL

PRODUCT DATA SHEET

1. RECOMMENDED USES

- 1.1. A premium quality tough polyurethane enamel for use on interior and exterior surfaces.
Ideal for use on suitably primed plastered walls, wood and metal surfaces.
- 1.2. The perfect product for bathroom walls and ceilings requiring a low sheen finish.

2. PREPARATION

- 2.1. Surfaces must be clean and free from loose material.
- 2.2. Surfaces should be correctly primed utilising surface preparation specifications recommended by the manufacturers.
- 2.3. May be applied directly onto cleaned previously painted surfaces.

3. APPLICATION

- 3.1. With either a short nap mohair roller or brush.
- 3.2. Should not be thinned or stirred as this will break down the gel structure.

4. PRODUCT DATA

TYPE	Polyurethane Alkyd
DFT\Coat	Min 25µm. Max 35µm
DRYING TIME	Surface Dry 1 Hour Hard Dry 8 hours at 25°C
VISCOSITY	70 -75 Ku
SPECIFIC GRAVITY	1.22
SOLIDS	61% by mass; 43% by volume
SPREADING RATE	9m ² /l (typical) depending on surface porosity and texture.
FINISH	Low sheen
CLEANUP	Mineral Turps

5. COLOUR

- 5.1. Available in white, black and a range of colours.
- 5.2. Pastel, Medium and Dark Tones can be tinted on request.

6. PRECAUTIONS

- 6.1. Do not apply to bare (unprimed) metal surfaces.
- 6.2. Do not paint in wet or cold weather (Minimum 5° Celcius)
- 6.3. When coating friable or plastered surfaces apply a generous coat of Alkali Resistant Plaster Primer.

DISCLAIMER

The above information is given in good faith but without warranty due to the fact that the methods of application, location and condition of the substrates being coated are beyond our control.