



Valdisole
704 - 706 6th Street
Wynberg
Santon 2090
Tel: (011) 885 3136
Fax: (011) 885 1719

WATERPROOFING COMPOUND (WITH FIBRE)

PRODUCT DATA SHEET

1. RECOMMENDED USES

- 1.1. Can be used as supplied as a fibre filled water proofing compound.
- 1.2. Should be used mainly on parapet walls gutters flashing and any other small areas that require waterproofing.
- 1.3. Can be overcoated with most water based acrylic finishes.

2. PREPARATION

- 2.1. Surfaces must be clean and free from loose material.
- 2.2. Surfaces should be correctly primed utilising surface preparation specifications recommended by the manufacturers.
- 2.3. May be applied directly onto cleaned previously painted surfaces.

3. APPLICATION

- 3.1. With a sheepskin roller or brush.
- 3.2. Dillution not recommended.

4. PRODUCT DATA

TYPE	Modified Acrylic
WATER RESISTANCE	Excellent
DRYING TIME	Hard Dry 18 hours at 25°C Overcoating time 24 hours plus.
VISCOSITY	Thixotropic Paste
RELATIVE DENSITY	1.30 - 1.35
SOLID BY MASS	55%
SPREADING RATE	±3m ² /l (typical) depending on surface porosity and texture.
FINISH	Satin Sheen Fibrous Texture.
CLEANUP	Water

5. COLOUR

- 5.1. Mid grey

6. PRECAUTIONS

- 6.1. Do not apply to bare (unprimed) metal surfaces.
- 6.2. Do not paint in wet or cold weather (Minimum 8° Celcius)

DISCLAIMER

The above information is given in good faith but without warranty due to the fact that the methods off application, location and condition of the substrates being coated are beyond our control.