

## Backwater valves *Staufix*<sup>®</sup> according to EN 12056

### Illustration and dimensioned drawing

### Article description

Outer diameter Ø (mm)	Art. #
--------------------------	--------

Installation area 650 x 300 mm

**Twin flap backwater valve *Staufix*<sup>®</sup> with emergency closure**  
made of polymer, Ø .....

Twin flaps, self-closing, one of which can be locked by hand as an emergency closure.

Inlet/outlet for connection to PVC pipe according to DIN 19534.

Ø 110	L: 355	H: 180 + 25	A x B: 205 x 155 mm
Ø 125	L: 405	H: 240 + 40	A x B: 270 x 200 mm
Ø 160	L: 450	H: 240 + 40	A x B: 270 x 200 mm
Ø 200	L: 530	H: 278 + 50	A x B: 353 x 248 mm

**CE EN 13564 Type 2**

With 2 polymer flaps:

Ø 110	73100
Ø 125	73125
Ø 160	73150
Ø 200	73200

With 1 polymer flap and 1 stainless steel flap (Rodent protection):

Ø 110	73100R
Ø 125	73125R
Ø 160	73150R

Installation area 650 x 300 mm

**Single flap backwater valve *Staufix*<sup>®</sup> with emergency closure**  
made of polymer, Ø .....

Flap self-closing and can be locked by hand as an emergency closure.

Inlet/outlet for connection to PVC pipe according to DIN 19534.

Ø 100	L: 355	H: 180 + 25	A x B: 205 x 155 mm
Ø 110	L: 355	H: 180 + 25	A x B: 205 x 155 mm
Ø 125	L: 405	H: 240 + 40	A x B: 270 x 200 mm
Ø 160	L: 450	H: 240 + 40	A x B: 270 x 200 mm
Ø 200	L: 530	H: 278 + 50	A x B: 353 x 248 mm

**CE EN 13564 Type 1**

With 1 polymer flap:

Ø 100	77100
Ø 110	72100
Ø 125	72125
Ø 160	72150
Ø 200	72200

With 1 stainless steel flap (Rodent protection):

Ø 110	72100R
Ø 125	72125R
Ø 160	72150R

Installation area 650 x 300 mm

**Single flap backwater valve *Staufix*<sup>®</sup>**  
made of polymer, Ø .....

Flap self-closing.

Inlet/outlet for connection to PVC pipe according to DIN 19534.

Ø 100	L: 355	H: 170	A x B: 205 x 155 mm
Ø 110	L: 355	H: 170	A x B: 205 x 155 mm
Ø 125	L: 405	H: 230	A x B: 270 x 200 mm
Ø 160	L: 450	H: 230	A x B: 270 x 200 mm
Ø 200	L: 530	H: 278	A x B: 353 x 248 mm

**CE EN 13564 Type 0**

Ø 100	76100
Ø 110	71100
Ø 125	71125
Ø 160	71150
Ø 200	71200

Installation area 650 x 300 mm

**Clean out *Staufix*<sup>®</sup>**  
made of polymer, Ø .....

upgradeable to backwater valve

Ø 110	L: 355	H: 170	A x B: 205 x 155 mm
Ø 125	L: 405	H: 230	A x B: 270 x 200 mm
Ø 160	L: 450	H: 230	A x B: 270 x 200 mm
Ø 200	L: 530	H: 278	A x B: 353 x 248 mm

Ø 110	70100
Ø 125	70125
Ø 160	70150
Ø 200	70200