

## Ivory 312 Road Stud Adhesive

### Description

An epoxy tar adhesive.

### Uses

Used for fixing "cats-eyes" onto road surfaces, creating rumble strips, bonding concrete kerb stones to asphalt surface and other non structural applications.

### Benefits

- Good weather resistance.
- Rapid cure.
- Convenient mix ratio.
- Good chemical resistance.
- Resists attack by petroleum products.
- Can cure on damp surfaces.

### Preparation

All surfaces to be free of dust, road dirt and oil.

### Application

Using volumes strictly in accordance with the given mixing ratio thoroughly mix the two components on a flat piece of wood or board with a putty knife or spatula.

- Apply the mixed material with a putty knife or pour into the required hole.
- If the mixed material is not used within 20 minutes of mixing, it will become unusable.
- Clean equipment immediately after use with Ivory Water Soluble Brush Cleaner.

### Technical Information

The figures that follow are typical properties achieved in laboratory tests at 20 °C and at 50% Relative Humidity.

No of components	:	2
Colour	:	Charcoal
Mixing Ratio by volume	:	2:1
Pot life (250ml @ 25°C)	:	25 - 30 mins
Cure Time	:	
Practical	:	2 hours
Full	:	12 hours
Application Temperature	:	Min 10°C Max 35°C
Cleaner	:	W.S.B.C.
Thinners	:	Do not thin
Shelf Life	:	12 months

### Health & Safety

Some of the components of this product may be hazardous during mixing and application. Please consult the relevant Health & Safety Data Sheet available from Flowcrete on request and sent with each delivery.

Flowcrete SA (Pty) Ltd  
176 Voortrekker Street  
Jacobs  
Durban  
Kwa Zulu Natal  
Tel: +27 31 461 3411  
Fax: +27 31 461 3475

Flowcrete SA (Pty) Ltd  
47 Forge Road  
Spartan  
Gauteng  
Tel: +27 11 394 1980  
Fax: +27 11 394 3003

Flowcrete SA (Pty) Ltd  
1A Gabriel place  
Cnr Gabriel & Main Road  
Plumstead  
Cape Town  
Tel: +27 21 797 0214  
Fax: +27 21 761 6664