

Conrep Bondex Bonding agent/Reinforcement Primer

Description

One component, cementitious polymer modified bonding agent / primer.

Uses

- · A bonding agent for cementitious repair
- Corrosion protection for steel reinforcement.

Benefits

- Easy to mix with water.
- User friendly.
- Imparts grab for patching mortars.
- Good water and chloride barrier.
- High bond strength.

Substrate Requirements

Surfaces to be clean, sound and free from contaminants. All repair areas should be defined by a 10mm saw cut to avoid feather edging. Presoak prepared area with clean water but avoid ponding. All steel should be sand blasted to remove all contaminants such as rust.

Application

Prior to the application of a repair mortar, Conrep Super Plaster, Conrep Super Screed or Conrep Mortar 50 prime with Conrep Bondex using a stiff bristle brush. Work in well to ensure complete wetting of concrete.

Precautions

- · Wear dust mask.
- Wear protective gloves.
- Avoid prolonged skin contact.
- Conrep Bondex is non toxic and can be washed off with fresh water.

Technical Information

The figures that follow are typical properties achieved in laboratory tests at 20 °C and at 50% Relative Humidity.

No of components:

Mixing ratio: ±5l water / 25kg

Yield: 14 ℓ ±1m²/{ Coverage: Colour: Grey Water Cleaner: Shelf Life: 6 months

Health & Safety

Some of the components of this product may be hazardous during mixing and application. Please consult the relevant Health & Safety Data Sheet available from Flowcrete on request and sent with each delivery.

Installation Service

The installation should be carried out by a Flowcrete approved contractor with a documented quality assurance scheme. Obtain details of our approved contractors by contacting our customer service team or enquiring via our web site www.flowcrete.com.

Important Note

Flowcrete's products are guaranteed against defective materials and the finished product.

Further Information

To ensure you are specifying a fit for purpose flooring for your project please consult our Technical Advisors on the number below or visit our website to register your interest in specifying one of the most durable floors on the market.

Flowcrete SA (Ptv) Ltd 176 Voortrekker Street Jacobs Durban Kwa Zulu Natal

Tel: +27 31 461 3411 Fax: +27 31 461 3475 Flowcrete SA (Pty) Ltd 47 Forge Road Spartan Tel: +27 11 394 1980

Fax: +27 11 394 3003

Flowcrete SA (Pty) Ltd 1A Gabriel place Cnr Gabriel & Main Road Plumstead Cape Town

Tel: +27 21 797 0214 Fax: +27 21 761 6664

2008.02 01 South Africa