

[Type here]

# PAINTCOR

SUPREME QUALITY *Since 1986*

2020 Revision

## ACRYLUNDER

### Description and application

#### CATEGORY

Undercoat / Filler coat

#### DESCRIPTION

AcrylUnder Acrylic Undercoat is specifically formulated as a quality undercoat that can be applied directly to good quality, cured cement plaster, or as a filler coat to primed plaster. AcrylUnder has excellent adhesion and filling properties with no added lead and low VOC.

#### FEATURES

- Excellent binding.
- Resistance to Alkali.
- Good hiding power.
- Good film building properties and can be used as a filler coat.

#### AREAS OF USE

- Filler coat
- Cement Plaster Primer
- Ceiling Paint

#### SURFACE PREPARATION AND APPLICATION

1. Brush the raw plaster to remove any loose friable particles.  
If the plaster is poor (loose and friable), apply 1 coat of Paintcor AcrySeal Acrylic Sealer diluted 1:1 with water and allow to dry.
2. Apply 1 coat of Paintcor's AcrylUnder by brush, roller or airless spray. Allow to dry.
3. Apply top coats of your choice.

**Note:** If AcrylUnder has been tinted to a colour on request, please ensure no water is added to the product as this will affect the colour.

[Type here]

# PAINTCOR

SUPREME QUALITY *Since 1986*

## APPLICATION EQUIPMENT

Apply by Brush, Sheepskin/Synthetic Roller or Spray

## CLEANING EQUIPMENT

Clean all equipment with water after use.

## STORAGE

Keep stored in cool, dry conditions and away from children.