

[Type here]

PAINTCOR

SUPREME QUALITY *Since 1986*

2020 Revision

ECONOCRYL

Description and Application

CATEGORY

Undercoating / Wall Coating / Ceiling Paint

DESCRIPTION

Econocryl Contractor's Acrylic is an economic product which allows both hiding power and maintenance at a low cost without drying to an under-bound chalking surface. Econocryl is perfect for the lower-budget paint jobs and can be over-coated at a later stage with a higher quality wall coating if required.

FEATURES

- Good alkalinity resistance and can be used directly on cured, good quality plaster.
- Ultra-matt finish.
- Breathable coating.

AREAS OF USE

- Basement parking walls
- Low cost developments
- Ceilings

SURFACE PREPARATION AND APPLICATION

New Plaster

1. Remove all loose or friable materials from the surface area.
2. Apply 1 coat of Paintcor AcrySeal diluted 1:1 with water to all new plaster. Allow 20 minutes @25 degrees c to dry.
3. Apply 2 coats of Econocryl. Allow to dry between coats.

Old Previously Plaster

1. Check the adhesion of the existing paint. If it is poor, remove all loose, peeling paint. Apply 1 coat of Paintcor AcrySeal diluted 1:1 with water to all areas to be painted. Allow to dry.
2. If the surface area is powdery, wash to remove all powder before applying one coat of Paintcor's AcrySeal Acrylic Sealer diluted 1:1 with water. Allow to dry.

[Type here]

PAINTCOR

SUPREME QUALITY *Since 1986*

3. Apply 2 coats of Econocryl. Allow to dry between coats.
4. If the adhesion of the old paint is good, wash walls down to remove all dirt and dust and allow to dry, then apply one or two coats of Paintcor's Econocryl.

APPLICATION EQUIPMENT

Apply by Brush, Sheepskin/Synthetic Roller or Spray

CLEANING EQUIPMENT

Clean all equipment with water after use.

STORAGE

Keep stored in cool, dry conditions and away from children.