

# PAINTCOR

2020 Revision

## Description and Application

## Primer

Glazed Tile Primer has been specially formulated as a primer for glazed ceramic tiles. It allows you to paint over bathroom and kitchen tiles, saving you the cost of retiling.

- Excellent Adhesion.
- Can be subjected to steam and water within 24 hours (at  $\pm 25^{\circ}\text{C}$ ) of applying your final topcoat.
- Glazed Tile Primer allows you to paint over bathroom and kitchen tiles, saving you the cost of retiling.

- Priming glazed tiles before painting
- Can be used to prime Melamine, PVC plastic and Glass (not subjected to water)
- Can be used in bathrooms and kitchens

1. Wash tiles down with soap and water. Allow to dry.
2. Scrub grouting and tiles with Paintcor's Ushevu (see Ushevu Data sheet) to kill algae, specifically focusing on the grouting. Rinse well and allow to dry.
3. Finally wipe tiles down with lacquer thinners or methylated spirits to ensure thorough cleaning of all grease from the tiles.
4. Apply 1 coat of Paintcor's Glazed Tile Primer to the clean dry tiles. Allow to dry. Apply Paintcor's Glazed Tile Primer by brush or roller to an even consistency. Take care not to apply the product too thick.
5. Apply 2 top coats of either Paintcor's EnviroCoat, Elegance or EnduraCoat in the desired colour of choice. Ensure NOT to use a lower grade product as a top coat in a bathroom or kitchen.

[Type here]

# PAINTCOR

SUPREME QUALITY *Since 1986*

6. **Allow this system at least 24 hours to dry before subjecting it to excessive humid or wet conditions. This system can take up to 7 days to reach full adhesion.**

**NOTE:** Cover the surface to which Glazed Tile Primer is being applied evenly. Do not attempt to spread Glazed Tile Primer too far as this will give a poor streaky finish.

## APPLICATION EQUIPMENT

Apply by Brush, Mohair or Sponge Roller

## CLEANING EQUIPMENT

Clean all equipment with water immediately after use.

## STORAGE

Keep stored in cool, dry conditions and away from children.