

PAINTCOR

SUPREME QUALITY *Since 1986*

2020 Revision

SATINTEX

Description and Application

CATEGORY

Wall Coating

DESCRIPTION

Satintex has been formulated using specialised raw materials to achieve a tough coating with a smooth textured finish. Satintex has been designed to cover plaster imperfections, with excellent adhesion, flexibility, water and alkali resistance. Satintex can be used as a first coat on good quality, cured plaster. Satintex can be tinted in a variety of colours and can be over coated with a final coat if required.

FEATURES

- Satintex is non-yellowing, odourless, non-toxic and enviro-friendly.
- For use on interior or exterior walls.
- Available in a wide range of colours.
- Can be applied directly to good quality, cured plaster as a primer.
- Excellent flexibility
- Gives a smooth texture with high film build.
- Excellent resistance to hairline cracking

AREAS OF USE

- Interior and Exterior walls
- Hiding bad plaster imperfections
- Combatting hairline cracks

SURFACE PREPARATION AND APPLICATION

New Plaster

1. Remove all loose friable material.
2. Satintex can be applied directly to good quality, cured plaster.
3. If the plaster is very friable then apply 1 coat of Paintcor's AcrySeal Acrylic Sealer diluted 1:1 with water to all new plaster. Allow to dry for 30 minutes @ 25 degrees C.
4. Apply 1 or 2 coats of Paintcor's Satintex by brush or roller

PAINTCOR

SUPREME QUALITY *Since 1986*

Previously Painted Plaster

Check adhesion of existing paint. (Cross hatch method) Using a Stanley knife, cut through the paint surface to the substrate vertically and horizontally approximately 3mm apart, creating little squares. If the edges of the squares curl up, and the square can easily be removed, this means the adhesion of the old paint system is failing.

If adhesion is poor:

1. Remove all old paint back to existing plaster.
2. If surface is powdery (chalking), wash to remove all powder. Allow to dry.
3. Apply 1 coat of Paintcor's AcrySeal Acrylic Sealer diluted 1:1 with water to all exposed plaster and washed chalking surfaces. Allow to dry.
4. Apply 1 or 2 coats of Paintcor's Satintex by brush or roller

If adhesion is good:

1. Wash walls to remove all dirt and dust. Allow to dry.
2. Apply Satintex as per no 4 above

Applying Satintex correctly requires professional painters with knowledge of applying textured finishes. Incorrectly applied Satintex will give a poor, uneven finish. Please contact our Technical Department for training on application of textured coatings. Avoid applying Satintex in Direct sunlight or when ambient temperatures are 30°C or above.

TIPS ON TEXTURES

- Work Quickly.
- Keep a wet edge at all times.
- Work corner to corner, do not stop in the middle of the wall.
- Use scaffolding on double story walls with two applicators meeting each other's wet edge.

APPLICATION EQUIPMENT

Apply by Brush or Sheepskin/Synthetic Roller.

CLEANING EQUIPMENT

Clean all equipment with water immediately after use.

STORAGE

Keep stored in cool, dry conditions and away from children.

PAINTCOR

SUPREME QUALITY *Since 1986*

Paintcor cc
Reg No: CK 86/19456/23
VAT No: 4830119311
Members: G. Williams, G. Adendorff
W. Williams

Head office: 1494 Mailship
street, Laser Park, Honeydew, 2040
Postal Address: P.O. Box 917,
Northriding, 2162
RSA

Email
sales@paintcor.co.za
Website
www.paintcor.co.za

Tel: 011 794 2885
Fax no: 011 794 6955
Emergency Numbers
+27(0) 79 526 1565
+27(0) 84 305 5636



SABS
ISO 9001 CERTIFIED

