

PAINTCOR

SUPREME QUALITY *Since 1986*

2020 Revision

SEALERMIX

Description and Application

CATEGORY

Undercoat/Sealer

DESCRIPTION

Sealermix is a pigmented, alkali resistant plaster-sealer specially designed for scratch plaster but can be used on any new masonry plaster.

FEATURES

- Reduces the high absorption of paint on scratch plaster.
- Good alkali resistance.
- Excellent binding power.
- Improves the quality of the plaster and the paint system.
- Pigmented to assist with the hiding power of subsequent coats.
- Can be applied to all types of plaster, cement or concrete.

AREAS OF USE

- Interior and Exterior masonry plaster
- Scratch or Smooth Plaster

SURFACE PREPARATION AND APPLICATION

1. Brush the scratch or normal plaster to remove all loose and friable materials.
2. Apply one liberal coat of Sealermix. Allow sufficient time to dry.
3. Apply one coat of Paintcor's Acrylunder acrylic undercoat. Allow sufficient time to dry. Undercoat is only necessary to obtain a smoother finished on new plaster.
4. Apply top coats of your choice. Allow to dry between coats.

APPLICATION EQUIPMENT

Apply by Brush, Sheepskin/Synthetic Roller or Spray

CLEANING EQUIPMENT

Clean all equipment with water after use.

PAINTCOR

SUPREME QUALITY *Since 1986*

STORAGE

Keep stored in cool, dry conditions and away from children.