

# PAINTCOR

SUPREME QUALITY *Since 1986*

2020 Revision

## SUBTEX

### Description and Application

#### CATEGORY

Undercoat

#### DESCRIPTION

SubTex has been specially formulated to correct texture differences on new one coat cement plaster. It has been designed to be cost effective, alkaline resistant and can be applied with either sheepskin roller to correct texture difference, or with a ripple roller to give a smooth low-relief ripple. SubTex will cover plaster in one coat when used with a sponged ripple roller. After application of Subtex, top coats of your choice can be applied.

#### FEATURES

- It is cost effective.
- It has a high binding power and excellent hiding power.
- It is alkaline resistant.
- It has the ability to cover texture differences in new plaster, preventing a patchy finish.
- It is also an Undercoat.

#### AREAS OF USE

A primer coat for smooth, good quality plaster. SubTex is a textured primer coat which improves texture consistency, helping to hide texture differences on your projects end result, specifically when using a sheen final coat.

#### SURFACE PREPARATION AND APPLICATION

##### NEW ONE-COAT WOOD FLOATED PLASTER

1. Remove all loose or friable materials from the plaster by dry brushing.
2. Seal the plaster with 1 coat of Paintcor's AcrySeal acrylic sealer, diluted 1:1 with water. Allow sufficient time to dry.
3. NOTE: Always seal new plaster with AcrySeal when applying SubTex with a ripple roller.
4. Apply one coat of Subtex with a sheepskin roller to correct plaster texture

OR

# PAINTCOR

SUPREME QUALITY *Since 1986*

OR

5. Apply one coat of Subtex with a ripple roller (sponge roller) to cover scarring and texture differences.
6. Finally apply top coats of your choice. Allow to dry between coats.

Note: Applying textured coatings with a sponge roller requires experienced applicators. Please call us for training if required.

## APPLICATION EQUIPMENT

Apply by Brush or Sheepskin/Synthetic/Ripple Sponge Roller

## CLEANING EQUIPMENT

Clean all equipment with water after use.

## STORAGE

Keep stored in cool, dry conditions and away from children.