

PAINTCOR

SUPREME QUALITY *Since 1986*

2020 Revision

ACRYLUNDER

Technical Specifications

Vehicle Type	Styrene Acrylic
Solvent	Water
Enviro Rating	13.8 grams VOC per litre (Conforms to Greenstar ratings)
Dilution / Thinning	No more than 10% water for spraying
Theoretical Spread Rate	6 - 8m ² per litre
Apply with	Brush, roller or spay
Drying time	@ 25°C ± 1 hour per coat
Wash ability	N/A
Elongation	N/A
Pigment	Pigmented
Solids Volume	± 45
Flexibility	N/A
Colour	White
Finish	Matt
Storage	Cool, dry place
Over coating	Top coat of your choice
Packaging	1L, 5L, 20L
Guarantee	N/A
Conditions of Guarantee	N/A
Resistance to Water	Fair
Resistance to Solvents	N/A
Impact Resistance	N/A
Active Ingredient	N/A
Additional Amount	N/A
Caution	Safe, Non-Toxic, Non-Flammable
Catalyst Ratio	N/A
Recommended Dry Film	55 micron per coat
Freeze Thaw	Pass
Accelerated Stability	N/A
Accelerated Weathering	N/A
Appearance	White Emulsion Paint

Note: VOC's are calculated on specific raw materials used in the product which contain VOC's, namely Glycol, Amine and free monomers.

PAINTCOR

SUPREME QUALITY *Since 1986*

Paintcor cc
Reg No: CK 86/19456/23
VAT No: 4830119311
Members: G. Williams, G. Adendorff
W. Williams

Head office: 1494 Mailship
street, Laser Park, Honeydew, 2040
Postal Address: P.O. Box 917,
Northriding, 2162
RSA

Email
sales@paintcor.co.za
Website
www.paintcor.co.za

Tel: 011 794 2885
Fax no: 011 794 6955
Emergency Numbers
+27(0) 79 526 1565
+27(0) 84 305 5636



SABS
ISO 9001 CERTIFIED

