## PAINTCOR

SUPREME QUALITY Since 1986

2020 Revision

## **ELEGANCE SILK**

## **Technical Specifications**

Vehicle Type Pure Acrylic (Adhesion Promoted)

Solvent

26.5g/L of VOC (Conforms to EU 2010 V.O.C. rules) **Enviro Rating** 

Dilution / Thinning Supplied ready for use

**Theoretical Spread Rate** 10m<sup>2</sup> per litre

NB: A MINIMUM OF 2 COATS TO BE APPLIED

Apply with Brush, Roller or spray

Drying time @ 25°C @ ±1 hour per coat

Wash ability Excellent Elongation 200% **Pigment Pigmented** Solids Volume 32% Flexibility Excellent

Colour Colours of your choice

Finish Matt

Cool, dry place Storage

Over coating N/A **Packaging** 1L, 5L, 20L Guarantee 10 Years

Conditions of Guarantee Products to be applied to manufacturer's specifications.

Areas below damp-proof course, boundary walls and structural defects are not

covered by this guarantee.

Resistance to Water Excellent **Resistance to Solvents** Good Good Impact Resistance **Active Ingredient** N/A **Additional Amount** N/A

Caution Safe, Non-Toxic, Non-Flammable

Catalyst Ratio N/A

Recommended Dry Film 30 micron (min) per coat

Freeze Thaw Pass Accelerated Stability **Pass Accelerated Weathering** Excellent **Appearance Emulsion** paint

Note: Elegance is an adhesion promoted product and can be applied to a wide variety of surfaces, including old enamel and certain plastics. VOC's are calculated on specific raw materials used in the product which contain VOC's, namely Glycol, Amine and free monomers.



## PAINTCOR

SUPREME QUALITY Since 1986

W. Williams

www.paintcor.co.za





