

PAINTCOR

SUPREME QUALITY *Since 1986*

2020 Revision

ENVIROCOAT

Technical Specifications

Vehicle Type	Ambient temperature cross-linking pure acrylic
Solvent	Water
Enviro Rating	56.4g/L of VOC (Conforms to Greenstar Rating for Gloss Trim Paint)
Dilution / Thinning	Supplied ready for use
Theoretical Spread Rate	±10m ² per litre
Apply with	Brush, Roller or spray
Drying time	@ 25°C ± 20 minutes to touch dry
Overcoating time	1 hour @ 25°C
Elongation	200%
Pigment	Pigmented
Solids Volume	36%
Flexibility	Excellent
Colour	Colour of your choice
Finish	Medium Gloss
Storage	Cool, dry place.
Washability	Excellent
Packaging	1L, 5L and 20L
Guarantee	10 Years
Conditions of Guarantee	Product to be applied to manufacturers specifications Areas below damp-proof course, boundary walls and defects are not covered by this guarantee
Resistance to Water	Excellent
Resistance to Solvents	Good
Impact Resistance	N/A
Active Ingredient	N/A
Additional Amount	N/A
Caution	Safe, Non-Toxic, Non-Flammable
Catalyst Ratio	N/A
Recommended Dry Film	35um per coat
Freeze Thaw	Pass
Accelerated Stability	Pass
Accelerated Weathering	Excellent
Appearance	Emulsion Paint

Note: EnviroCoat is a water-based enamel substitute, with no added lead, low VOC rating for Trim Gloss Finishes, suitable for hospitals, children's cots, toys, etc. VOC's are calculated on specific raw materials used in the product which contain VOC's, namely Glycol, Amine and free monomers.

Paintcor cc

Reg No: CK 86/19456/23

VAT No: 4830119311

Members: G. Williams, G. Adendorff
W. Williams

Head office: 1494 Mailship
street, Laser Park, Honeydew, 2040
Postal Address: P.O. Box 917,
Northriding, 2162
RSA

Email
sales@paintcor.co.za

Website
www.paintcor.co.za

Tel: 011 794 2885
Fax no: 011 794 6955
Emergency Numbers
+27(0) 79 526 1565
+27(0) 84 305 5636



SABS
ISO 9001 CERTIFIED

