## PAINTCOR

SUPREME QUALITY Since 1986

2020 Revision

## FLASHPATCH EXTERIOR

## **Technical Specifications**

Vehicle Type Modified Acrylic

Solvent Water

Enviro Rating 19g/L of VOC (Conforms to EU 2010 V.O.C. rules)

Dilution / Thinning Supplied ready for use

Theoretical Spread Rate N/A

Apply with Trowel, Scraper

Drying time ± 6 hours @ 25°C - 5mm thick

Wash ability N/A
Elongation Good
Pigment N/A

Viscosity at 25°C Thick paste

Solids Volume 63%
Flexibility Good
Colour Grey white
Finish Smooth

Storage Cool, dry place.

Over coating Undercoat or top coat of your choice

Packaging 250ml, 500ml, 1L, 5L and 20L

Guarantee N/A
Conditions of Guarantee N/A

Resistance to Water Very good

Resistance to Solvents Fair
Specific Gravity 1.82
Impact Resistance Good
Active Ingredient N/A
Additional Amount N/A

Caution Safe, Non-toxic, Non-flammable

Catalyst Ratio N/A
Recommended Dry Film 3 – 4mm
Freeze Thaw Pass
Accelerated Stability Pass
Accelerated Weathering N/A

Appearance Thick white grey paste

Note: Do not patch more than 5mm depth at a time. VOC's are calculated on specific raw materials used in the product which contain VOC's, namely Glycol, Amine and free monomers.





RSA

Tel: 011 794 2885

## PAINTCOR

SUPREME QUALITY Since 1986

RSA





