

PAINTCOR

SUPREME QUALITY *Since 1986*

2020 Revision

GLAZED TILE PRIMER

GTP

Technical Specifications

| | |
|-------------------------|---|
| Vehicle Type | Modified Pure Acrylic |
| Solvent | Water |
| Enviro Rating | Conforms to EU 2010 V.O.C. Rules |
| Dilution / Thinning | Supplied ready for use Glazed Tile Primer can be thinned with $\pm 5\%$ of water for spray application |
| Theoretical Spread Rate | 10m ² per litre |
| Apply with | Brush, Roller or Spray |
| Drying time | @ 25°C - 45 minutes Overcoat |
| Wash ability | N/A |
| Elongation | Good |
| Pigment | Pigmented |
| Solids Volume | ± 32 |
| Flexibility | Good |
| Colour | White |
| Finish | Eggshell |
| Storage | Cool, dry place. |
| Over coating | EnviroCoat, Elegance, EnduraCoat, HiGlo, LoGlo only |
| Packaging | 1L, 5L and 20L |
| Guarantee | N/A |
| Conditions of Guarantee | N/A |
| Resistance to Water | Good |
| Resistance to Solvents | N/A |
| Impact Resistance | N/A |
| Active Ingredient | N/A |
| Additional Amount | N/A |
| Caution | Safe, Non-toxic, Non-flammable |
| Catalyst Ratio | N/A |
| Recommended Dry Film | 30 microns |
| Freeze Thaw | Pass |
| Accelerated Stability | Pass |
| Accelerated Weathering | N/A |
| Appearance | White emulsion paint |

Note: Follow all directions for use.

PAINTCOR

SUPREME QUALITY *Since 1986*

Paintcor cc
Reg No: CK 86/19456/23
VAT No: 4830119311
Members: G. Williams, G. Adendorff
W. Williams

Head office: 1494 Mailship
street, Laser Park, Honeydew, 2040
Postal Address: P.O. Box 917,
Northriding, 2162
RSA

Email
sales@paintcor.co.za
Website
www.paintcor.co.za

Tel: 011 794 2885
Fax no: 011 794 6955
Emergency Numbers
+27(0) 79 526 1565
+27(0) 84 305 5636



SABS
ISO 9001 CERTIFIED

