

PAINTCOR

SUPREME QUALITY *Since 1986*

2020 Revision

GRANTEX

Technical Specifications

Vehicle Type	Styrene Acrylic
Solvent	Water
Enviro Rating	Conforms to EU 2010 V.O.C. Rules
Dilution / Thinning	This product is supplied ready for Use 1. Semi Textured finish: (Application with conventional roller) No Dilution. 2. Ripple Texture (Application with a sponge stipple roller) No Dilution.
Theoretical Spread Rate	Ripple Finish (Sponge Roller) $\pm 2\text{-}2.5\text{m}^2$ per litre Granular-textured Finish (Sheep skin roller) $\pm 2\text{-}4\text{m}^2$ per litre
Apply with	Brush, Sponge or Lamb's wool roller
Drying time	@25°C – Touch dry ± 2 hours. Overcoat: ± 6 hours
Wash ability	Good
Elongation	100%
Pigment	Pigmented
Solids Volume	$\pm 58\%$
Flexibility	Fair
Colour	Colour of your choice
Finish	Granular Texture
Storage	Cool, dry place
Over coating	Not necessary, however Paintcor's Elegance for long term protection.
Packaging	1L, 5L, 20L
Guarantee	5 Years
Conditions of Guarantee	Product to be applied to manufacturer's specification. Areas below damp proof course, boundary walls and structural defects are not covered by this guarantee.
Resistance to Water	Good
Resistance to Solvents	Poor

Continue on next page...

PAINTCOR

SUPREME QUALITY *Since 1986*

Impact Resistance	Good
Active Ingredient	N/A
Additional Amount	N/A
Caution	Safe, Non-Toxic, Non-Flammable
Catalyst Ratio	N/A
Recommended Dry Film	Ripple finish: ± 200 microns (1 coat) Sheep skin: ± 140 microns per coat
Freeze Thaw	Pass
Accelerated Stability	Pass
Accelerated Weathering	Pass
Appearance	Thick Emulsion Coating

Note: *Do not apply Grantex with a textured roller unless the painters have been trained in rolling ripple. Contact our technical department should you require assistance.*