

PAINTCOR

SUPREME QUALITY *Since 1986*

2020 Revision

HIGLO

Technical Specifications

Vehicle Type	Long Oil Alkyd
Solvent	Turpentine
Enviro Rating	Flammable
Dilution / Thinning	Supplied ready for use
Theoretical Spread Rate	10m ² per litre
Apply with	Brush, Roller or Spray
Drying time	Surface Dry: 2 hours Hard Dry: 7 hours
Wash ability	Excellent
Elongation	N/A
Pigment	Pigmented
Solids Volume	± 40
Flexibility	Fair
Colour	Colour of your choice
Finish	High Gloss
Storage	Cool, dry place.
Over coating	N/A
Packaging	1L, 5L and 20L
Guarantee	N/A
Conditions of Guarantee	N/A
Resistance to Water	Excellent
Resistance to Solvents	Good
Impact Resistance	Pass
Active Ingredient	N/A
Additional Amount	N/A
Caution	Flammable (see Material Safety Data sheet)
Catalyst Ratio	N/A
Recommended Dry Film	35 - 40µm
Freeze Thaw	Pass
Accelerated Stability	Pass
Accelerated Weathering	Pass
Appearance	High gloss enamel paint

Note: *White will yellow in areas that are in continual darkness*