

PAINTCOR

SUPREME QUALITY *Since 1986*

2020 Revision

PLASTERPRIME TRADE

Technical Specifications

Vehicle Type	Solvent Base Acrylic
Solvent	Mineral Turpentine
Enviro Rating	Reduced V.O.C
Dilution / Thinning	Do not dilute
Theoretical Spread Rate	10 m ² per litre
Apply with	Brush, roller or spay
Drying time	Touch dry: @ 25°C – 1 hour / Over coating: 6 hours @ 25°C
Washability	N/A
Elongation	Fair
Pigment	Pigmented (Off-white)
Solids Volume	40%
Flexibility	Fair
Colour	White
Finish	Low sheen
Storage	Cool, dry place. Keep out of reach of children.
Over coating	Any of Paintcor's water based top coats.
Packaging	1L, 5L, 20L
Guarantee	N/A
Conditions of Guarantee	N/A
Resistance to Water	Excellent
Resistance to Solvents	Fair
Impact Resistance	Good
Active Ingredient	N/A
Additional Amount	N/A
Caution	Solvent base: Flammable
Catalyst Ratio	N/A
Recommended Dry Film	40 microns (maximum) per coat
Freeze Thaw	Pass
Accelerated Stability	Pass
Accelerated Weathering	N/A
Appearance	White paint

Note: For best performance, follow application instructions.