PAINTCOR

SUPREME QUALITY Since 1986

2020 Revision

ACRYSEAL

Technical Specifications

Vehicle Type Styrene Acrylic

Solvent Water

Enviro Rating 2.3g/L of VOC (Conforms to Greenstar Ratings)

Dilution / Thinning

Theoretical Spread Rate

Apply with

Drying time

Dilute 1:1 with water

10 - 12m² per litre

Brush, roller or spay

25°C - 30 minutes

Wash ability N/A Elongation N/A

Pigment Non-pigmented

Solids Volume \pm 22% Flexibility Excellent

Colour Clear when dry

Finish N/A

Storage Cool, dry place

Over coating AcrylUnder or top coat of your choice

Packaging 1L, 5L, 20L

Guarantee N/A
Conditions of Guarantee N/A

Resistance to Water Very good

Resistance to Solvents N/A
Impact Resistance N/A
Active Ingredient N/A
Additional Amount N/A

Caution Safe, Non-Toxic, Non-Flammable

Catalyst Ratio N/A
Recommended Dry Film N/A
Freeze Thaw Pass
Accelerated Stability N/A
Accelerated Weathering N/A

Appearance Milky White liquid

VOC's are calculated on specific raw materials used in the product which contain VOC's, namely Glycol, Amine and free monomers.



PAINTCOR

SUPREME QUALITY Since 1986

W. Williams

www.paintcor.co.za





