

PAINTCOR

SUPREME QUALITY *Since 1986*

2020 Revision

RIPPLETEX

Technical Specifications

Vehicle Type	Modified Acrylic
Solvent	Water
Enviro Rating	Conforms to EU 2010 V.O.C. Rules
Dilution / Thinning	This product is supplied ready for Use 1. Semi Textured finish: (Application with conventional roller) Thin with 10% water. 2. Spiky ripple finish: No dilution 3. Rounded Ripple finish: 5% water dependant on ambient temperature.
Theoretical Spread Rate	Ripple Finish (Sponge Roller) $\pm 2-2.5\text{m}^2$ per litre Semi-textured Finish (Sheep skin roller) $\pm 3.5 - 4\text{m}^2$ per litre
Apply with	Brush, Sponge or Lamb's wool roller
Drying time	@25°C – Touch dry ± 2 hours. Overcoat: ± 3 hours
Wash ability	Good
Elongation	200%
Pigment	Pigmented
Solids Volume	$\pm 54\%$
Flexibility	Good
Colour	Colour of your choice
Finish	Textured
Storage	Cool, dry place
Over coating	Not necessary, however Paintcor's Elegance for long term protection.
Packaging	1L, 5L, 20L
Guarantee	7 Years
Conditions of Guarantee	Product to be applied to manufacturer's specification. Areas below damp-proof course, boundary walls and structural defects are not covered by this guarantee.
Resistance to Water	Excellent
Resistance to Solvents	Fair

Continue on next page...

SUPREME QUALITY *Since 1986*

Note: Do not apply RippleTex with a textured roller unless the painters have been trained in rolling ripple. Contact our technical department should you require assistance.