

PAINTCOR

SUPREME QUALITY *Since 1986*

2020 Revision

SATINTEX

Technical Specifications

Vehicle Type	Modified Acrylic
Solvent	Water
Enviro Rating	Conforms to EU 2010 V.O.C. Rules
Dilution / Thinning	This product is supplied ready for Use
Theoretical Spread Rate	6m ² per litre
Apply with	Brush or Lamb's wool roller
Drying time	@25°C – Touch dry ± 2 hours. Overcoat: ±3 hours
Wash ability	Good
Elongation	100%
Pigment	Pigmented
Solids Volume	±54%
Flexibility	Excellent
Colour	Colour of your choice
Finish	Smooth Texture
Storage	Cool, dry place
Over coating	Not necessary, however Paintcor's Elegance for long term protection.
Packaging	5L, 20L
Guarantee	7 Years
Conditions of Guarantee	Product to be applied to manufacturer's specification. Areas below damp proof course, boundary walls and structural defects are not covered by this guarantee.
Resistance to Water	Excellent
Resistance to Solvents	Poor

Continue on next page...

Paintcor cc

Reg No: CK 86/19456/23

VAT No: 4830119311

Members: G. Williams, G. Adendorff
W. Williams

Head office: 1494 Mailship
street, Laser Park, Honeydew, 2040
Postal Address: P.O. Box 917,
Northriding, 2162
RSA

Email
sales@paintcor.co.za

Website
www.paintcor.co.za

Tel: 011 794 2885
Fax no: 011 794 6955

Emergency Numbers
+27(0) 79 526 1565
+27(0) 84 305 5636



SABS
ISO 9001 CERTIFIED



PAINTCOR

SUPREME QUALITY *Since 1986*

Impact Resistance	Good
Active Ingredient	N/A
Additional Amount	N/A
Caution	Safe, Non-Toxic, Non-Flammable
Catalyst Ratio	N/A
Recommended Dry Film	90 micron per coat
Freeze Thaw	Pass
Accelerated Stability	Pass
Accelerated Weathering	Pass
Appearance	Thick Emulsion Coating

Paintcor cc

Reg No: CK 86/19456/23

VAT No: 4830119311

Members: G. Williams, G. Adendorff
W. Williams

Head office: 1494 Mailship
street, Laser Park, Honeydew, 2040
Postal Address: P.O. Box 917,
Northriding, 2162
RSA

Email
sales@paintcor.co.za

Website
www.paintcor.co.za

Tel: 011 794 2885
Fax no: 011 794 6955

Emergency Numbers
+27(0) 79 526 1565
+27(0) 84 305 5636



SABS
ISO 9001 CERTIFIED

