

# PAINTCOR

SUPREME QUALITY *Since 1986*

2020 Revision

## STONESEAL

### Technical Specifications

Vehicle Type	Solvent Borne Pure Acrylic
Solvent	Xylene
Enviro Rating	Flammable
Dilution / Thinning	Supplied ready for use
Theoretical Spread Rate	± 20m <sup>2</sup> per liter (Sealed surface) Porous surface: ± 5m <sup>2</sup> - 10m <sup>2</sup> dependent on surface absorption
Apply with	Brush, Roller or Spray
Drying time	@ 25°C - ± 1 hour
Wash ability	Excellent
Elongation	N/A
Pigment	Non-Pigmented
Solids Volume	15%
Flexibility	Fair
Colour	Transparent
Finish	Clear
Storage	Cool, dry place. Keep out of reach of children.
Over coating	3 hours @ 25°C
Packaging	1L, 5L and 20L
Guarantee	N/A
Conditions of Guarantee	N/A
Resistance to Water	Excellent
Resistance to Solvents	Good
Impact Resistance	N/A
Active Ingredient	N/A
Additional Amount	N/A
Caution	Flammable (see Material Safety Data Sheet)
Catalyst Ratio	N/A
Recommended Dry Film	More coats applied will increase the gloss of the surface applied too.
Freeze Thaw	Pass
Accelerated Stability	Pass
Accelerated Weathering	N/A
Appearance	Transparent liquid

**Note:** Do not use in confined areas without the correct equipment. See Material Safety and Technical Specification Data Sheets. Do not try and apply this product at a thick rate, rather spread thin coats allowing drying time between each coat.