

# PAINTCOR

SUPREME QUALITY *Since 1986*

2020 Revision

## WOODLUSTA SUEDE / GLOSS

### Technical Specifications

Vehicle Type	Polyurethane
Solvent	Turpentine
Enviro Rating	Flammable 3
Dilution / Thinning	Supplied ready for use
Theoretical Spread Rate	15m <sup>2</sup> per litre
Apply with	Brush, Roller or Spray
Drying time	@25°C: 6 hours. Sand dry.
Wash ability	Excellent
Elongation	Good
Pigment	Non Pigmented
Solids Volume	38%
Flexibility	Good
Colour	Can be stained or left clear
Finish	Suede
Storage	Cool, dry place. Keep out of reach of children.
Over coating	N/A
Packaging	1L and 5L
Guarantee	N/A
Conditions of Guarantee	N/A
Resistance to Water	Very good
Resistance to Solvents	Good
Impact Resistance	N/A
Active Ingredient	N/A
Additional Amount	N/A
Caution	Flammable (see Material Safety Data sheet)
Catalyst Ratio	N/A
Recommended Dry Film	± 25 microns per coat. Apply at least two coats.
Freeze Thaw	N/A
Accelerated Stability	Pass
Accelerated Weathering	N/A
Appearance	Amber varnish