

# PAINTCOR

SUPREME QUALITY *Since 1986*

2020 Revision

## WOODLUV

### Technical Specifications

Vehicle Type	Linoleic Rich Flexible Long Oil Alkyds
Solvent	Turpentine
Enviro Rating	Flammable 3
Dilution / Thinning	Supplied ready for use
Theoretical Spread Rate	15m <sup>2</sup> per litre
Apply with	Brush, Roller OR Spray
Drying time	6 hours at 25°C
Wash ability	Excellent
Elongation	Excellent
Pigment	Non Pigmented
Solids Volume	36.5 %
Flexibility	Excellent
Colour	Can be stained or left clear
Finish	Gloss
Storage	Cool, dry place. Keep out of reach of children.
Over coating	N/A
Packaging	1L and 5L
Guarantee	N/A
Conditions of Guarantee	N/A
Resistance to Water	Excellent
Resistance to Solvents	Good
Impact Resistance	N/A
Active Ingredient	N/A
Additional Amount	N/A
Caution	Flammable / Fumes (see Material Safety Data sheet)
Catalyst Ratio	N/A
Recommended Dry Film	25µm per coat
Freeze Thaw	N/A
Accelerated Stability	Pass
Accelerated Weathering	Pass
Appearance	Pale amber varnish

**Note:** *This product must be used in conjunction with Paintcor's WoodFirst.*