

LAPSEAL

A compressible, self-adhesive, impregnated Polyurethane foam sealing strip.

APPLICATION



- Lapseal is used for waterproofing and dust proofing the side and end laps of roofing sheets.

ADVANTAGES

- Lapseal is clean and easy to use.
- Available in various material types and sizes.

PHYSICAL PROPERTIES / TECHNICAL DATA

- **Composition:** Metal Roofing Sheets: Flexible acrylic polymer-impregnated Polyurethane foam.
Fibre Cement Roofing Sheets: Flexible wax- and resin-impregnated Polyurethane foam.
- **Colour:** Grey.
- **Size:** Metal Roofing Sheets: 5 mm x 9 mm.
Fibre Cement Roofing Sheets: Big Six, Profile B, Canadian Pattern, Modulit, etc.: 10 mm x 20 mm; Canalit: 20 mm x 25 mm.
- **Weathering:** Retains memory and sealing qualities (if compressed).
- **Porosity:** Metal Roofing Sheets: Compress by 95 % of its original thickness for a waterproof seal.
Fibre Cement Roofing Sheets: Compress by 75 % of its original thickness for a waterproof seal.
- **Temperature Range:** Metal Roofing Sheets: -20 °C to +120 °C.
Fibre Cement Roofing Sheets: -20 °C to +77 °C.
- **Resistance:** Not sensitive to decay, fungi, weak acids or alkaline solutions.



DIRECTIONS FOR USE

- Ensure that roof sheets are free from dust, oil and grease.
- Peel the release paper from the self-adhesive and place Lapseal on the side and end laps of the roof sheets as required.
- Position Lapseal no less than 25 mm from the edge of the sheet.
- Position the roof sheet and bolt down.

Whilst this document has been prepared in good faith, Sondor Industries (Pty) Ltd accept no contractual liability of any kind to any person in respect of its contents or any use made thereof, nor must it be assumed that any such use will not infringe any patent. This document shall form no part of any contract with a customer. The data supplied on this sheet is typical and in no way reflects the final resultant values of the respective products.

sondor
PERFORMANCE FOAMS



CAPE TOWN: Tel: (021) 959 9400, Fax: (021) 959 9434, E-mail: ctn@sondor.co.za **DURBAN:** Tel: (031) 705 4220, Fax: (031) 705 4566, E-mail: dbn@sondor.co.za **JOHANNESBURG:** Tel: (011) 452 4530, Fax: (011) 452 4532, E-mail: jhb@sondor.co.za
PORT ELIZABETH: Tel: (041) 486 2231, Fax: (041) 486 2234, E-mail: pe@sondor.co.za **PRETORIA:** Tel: (012) 803 4471, Fax: (012) 803 4400, E-mail: pta@sondor.co.za **EXPORTS:** Tel: +27-21-959 5900, Fax: +27-21-959 5901, E-mail: exports@sondor.co.za
HEAD OFFICE: Tel: (021) 959 5900, Fax: (021) 959 5901, E-mail: ho@sondor.co.za **EAST LONDON AGENT –** Jonny Grant 043 7433067/68
BLOEMFONTEIN AGENT – Build OFS 051 435 4880